

# POWERING YOUR RELIABILITY



## Quality Line open with used engine

1500 r.p.m. 230/400 Volt, 50 Hz.

PL2							versie 2010.1	
output (stand-by)	engine	alternator	dimensions	empty weight	capacity tank	price generatorset	price AMF	
kVA	 type	 type	mm	kg	ltrs			
15	F2L912 used	SK160CB	1400x750	550	100	on request	on request	
25	F3L912 used	IB160SA	1400x750	550	100	on request	on request	
35	F4L912 used	IB160MA	1520x750	700	100	on request	on request	
53	F6L912 used	JB-SC IB-LA	2000x750	1000	140	on request	on request	
63	F6L913 used	JB200CA	2000x750	1000	140	on request	on request	
75	BF6L913 used	JB200CB	2200x800	1050	140	on request	on request	
100	F8L413 used	JB200LA	2100x1100	1500	300	on request	on request	
160	F10L413F used	SK250MS	2350x1300	2100	500	on request	on request	

- |  |            |
|--|------------|
| 1 Additional price drippan under the whole machine                           | on request |
| 2 Additional price cover for the exhaustbranche pipe incl. 10 mtrs. Glastape | on request |
| 3 Lesserprice when batterycharger is not needed                              | on request |

## Technical specification

### Standard delivery contains

- used Deutz engine, aircooled in 100% good technical condition
- new alternator, make Sincro, execution single-bearing, directly flanged to the engine
- engine and alternator are with anti/vibrationdampers mounted on a frame with integrated fuel tank
- new terminalboard provided with:
  - \* central steeringmodule with: start/stop for the engine, tension and frequencyreading, batterytensionreading, malfunctionreading
  - \* operationswitch: Hand - Off - Auto (matical)
  - \* batterycharger
  - \* emergencybutton
  - \* controllamps for mainswitch OUT and emergency IN
  - \* connections on terminal for start/stop command from a distance
  - \* mainswitch 3P
- motorsecurity built up for overtemperature and oilpressure by solenoid
- exhaustsystem contents: stainless steel expansion part, damper, 2 elbows, 2 mtr. rainpipe and rainvalve (delivered separately)
- set is complete with airfilter, drainpump for lubeoil and batteries
- sprayed in the colour RAL5010



### Conditions

Mentioned prices are excl. VAT  
 Changes in prices and currency are not withstanding  
 Applicable are the METAALUNIECONDITIONS  
 Guarantee- and paymentconditions and also deliverytime on request  
 Generatorsets are delivered free inside Holland (F.A.S.) (excl. isles).



Bredenoord Aggregaten bv

Postbus 20122 - 7302 HC Apeldoorn Holland - Zutphensestraat 319 - 7325 WT Apeldoorn Holland  
 Tel. +31(0)55 - 301 85 30 - Fax +31(0)55 - 301 85 90 - info@bredenoord.com - www.bredenoord.com