

# Mobile charging point Charge 11



- Charging at any location
- Two connections Type II
- 32A power supply

## Technical specifications\*

Product details	
<b>Measurements inc. frame</b>	1.300 x 800 x 2.700 mm (l x h x h)
<b>Weight</b>	190 kg
Technical specifications	
<b>Power</b>	Min. 3,7 kW up to Max 22 kW
<b>Rated voltage</b>	400 V (3 fases) 32 Ampère
<b>Socket/outlet</b>	2 Type II outlets (Mennekes plug) for simultaneous charging
<b>Connections</b>	10 meter cable with plug CEE 32 A
<b>Load balancing standard</b>	Yes
<b>Amenities</b>	Fork lift amenity and one central lifting eye
Other	
<b>Certificates &amp; approvals</b>	CE and TÜV
Description	
<p>Mobile charging point for charging electric vehicles at any location of your choice. The charging point can be used in combination with a grid connection, the Bredenoord Battery Box or a Bredenoord genset running exclusively on HVO biofuel.</p> <p>The charging point is equipped with two type II connections for simultaneous charging. Through load balancing the power is optimally divided between the sockets. The mobile charging point is plug &amp; play without a billing system for the users. Per your request the charging point can be personalized with your own logo. The mobile charging point is plug &amp; play without a billing system for the users.</p> <p>The charging point is easy to relocate and thereby ideal for allowing visitors and staff on construction sites, infrastructure projects and events to power their electric or hybrid car.</p>	

\* The information above applies to the pictured product. The delivered product can deviate from this

Do you want to know more about our products? We will gladly help and advise you, also for individual power solutions.